Martian Agricultural Systems Analysis

Frame the activity

Activity: Sowing, maintaining, and harvesting potatoes.
Person or people involved: Martian outpost farmer/astronaut.
Terrestrial setting: Commercial Earth greenhouse.
Selected habitat or extreme environment: Pressurized, climate-controlled agricultural dome on the Martian surface.
Reference status: Proposed concept / theoretical operational environment.
Start of the activity: Preparing the growing medium (Martian regolith or hydroponic trays) and planting seed potatoes.
End of the activity: Harvesting the mature potato tubers and clearing the biomass waste.
Inside our boundary: The farmer, hand tools, the potato crop, the immediate planter beds, local soil moisture/temperature sensors, and the irrigation drip lines touching the soil.

Important support outside our boundary: The base's primary nuclear or solar power grid, the central water recycling plant, and the dome's overarching life support system (HVAC, O2/CO2 scrubbing).
First source or observation to investigate: NASA Human Integration Design Handbook and agricultural studies on simulated Martian regolith.

Prepare the Resource and dependency map

Resource or support	What does it enable?	Provider, storage or maintenance	Evidence: F / E / A / ?
Water	Seed hydration, nutrient transport, and cellular growth.	Base water recycling plant; local reservoir tank.	F (Fact - Biological requirement)
Light	Photosynthesis and thermal regulation.	Artificial LED grow lights powered by the base grid (supplementing weak Martian sunlight).	A (Assumption - Natural sunlight is insufficient)
Nutrients (N-P-K)	Plant development in otherwise dead regolith.	Base compost system or imported chemical fertilizer stores.	F (Fact - Regolith lacks organic nutrients)
CO2 / Airflow	Carbon intake for leaves; prevents mold buildup.	Dome HVAC and life support scrubbers routing crew exhalations.	A (Assumption - Crew CO2 is routed to the greenhouse)

A relevant output or waste flow, and where it goes next: Transpired humidity from the potato leaves floats into the dome's air space, where it must be captured by dehumidifiers and routed back to the central water recycling plant. Inedible biomass (stems/leaves) goes to the base compost processor.

One shared resource that another activity also needs: Electrical power. The high-intensity grow lights compete directly with life support, rover charging, and scientific equipment.

One dependency to stress-test: Natural Martian sunlight. Mars receives roughly 43% of the sunlight Earth does, and global dust storms can block it for weeks.

What changes if it is unavailable or reduced: If natural light fails during a dust storm and the base grid cannot spare enough power for continuous artificial lighting, the crop yield plummets or dies, directly threatening the crew's food security.

What evidence would change our interpretation: Research demonstrating that potatoes can be genetically engineered to thrive in ultra-low light conditions without artificial supplementation.

C. Check an estimate

What is being estimated: Daily water requirement for the potato crop inside the boundary.

Unit and period, for example per use or per person per day: Liters per square meter of crop per day ($L/m^2/day$).

Source or basis: Terrestrial commercial hydroponic potato farming data, adapted for a closed-loop system.

Calculation or reasoning: If a terrestrial greenhouse uses roughly 3-5 $L/m^2/day$, the Martian system will require the same biological intake at the roots, but the overall system loss will be near zero if the dome's dehumidifiers successfully recapture 95%+ of the transpired moisture.

Assumptions and uncertainty: Assuming the ambient temperature remains constant and the dehumidification hardware does not fail.

Do we need demand, capacity or reserve? Explain which: Reserve. If the central water recycling plant goes offline for maintenance, the greenhouse local reservoir needs a multi-day reserve capacity to keep the crop alive until the main feed is restored.

Compare Earth with the selected extraterrestrial habitat or environment

Dependency	Earth condition	Habitat condition (Mars)	Consequence and design implication
Growing Medium (Soil)	Biologically active, nutrient-rich, naturally draining.	Martian regolith is biologically dead and contains toxic perchlorates.	Implication: Standard planting is impossible. The system must include a preliminary chemical washing process to remove perchlorates, followed by a biological inoculation phase using crew compost to create usable soil.
Gravity (Water flow)	1G pulls water steadily downward through the soil profile.	0.38G significantly alters capillary action, causing water to pool or drain unpredictably.	Implication: Traditional overhead watering or flooding will cause root rot or dry pockets. The irrigation system must be redesigned as a pressurized, sub-surface drip line or an aeroponic misting chamber to force water directly to the roots.
Atmospheric Pressure	1 ATM, naturally balanced CO2/O2 mix.	Near-vacuum outside; inside the dome, pressure and gas mix	Implication: The dome structure is a single point of failure. If

Dependency	Earth condition	Habitat condition (Mars)	Consequence and design implication
		are artificially maintained.	micro-meteorites breach the dome, instantaneous depressurization will flash-freeze and kill the crop. The design must incorporate automated, segmented blast doors to isolate damaged greenhouse modules.

Workshop 1: The Invisible Bill (Martian Potato Dependency Map)

1. System Boundary & Core Action

- Activity: Sowing, maintaining, and harvesting potatoes in a Martian agricultural dome.
- Inside Boundary: Farmer, hand tools, potato crop, planter beds, sensors, drip lines.
- Outside Boundary (Support): Base power grid, central water recycling, life support (HVAC).

2. The Dependency Map (Nodes & Arrows)

Water & Hydration Flow

- Central Water Recycling (*Outside Boundary*) -> supplies -> Local Dome Reservoir [E: 3-5 L/m^2/day reserve needed]
- Local Dome Reservoir -> pressurizes -> Sub-surface Drip Lines
- Sub-surface Drip Lines -> hydrates -> Potato Roots [F: Biological requirement]

Energy & Light Flow

- Base Nuclear/Solar Grid (*Outside Boundary*) -> powers -> LED Grow Lights
- LED Grow Lights -> enables -> Photosynthesis (Leaves) [A: Natural sunlight is insufficient]
- *Note on Arrow:* Mark the grid power arrow as "Shared Resource" (competes with rover charging/life support).

Air & Atmospheric Flow

- Base Crew Quarters -> exhales -> CO2
- CO2 -> routed via -> Dome HVAC Scrubbers [A: Crew CO2 is routed to greenhouse]
- Dome HVAC Scrubbers -> supplies -> Potato Leaves

Waste & Output Flow (Closing the Loop)

- Potato Leaves -> transpires -> Humidity / Air Moisture
- Humidity -> captured by -> Dehumidifiers
- Dehumidifiers -> returns to -> Central Water Recycling (*Outside Boundary*)
- Mature Potato Plant -> yields -> Tubers (Food) -> goes to -> Base Kitchen
- Mature Potato Plant -> yields -> Inedible Biomass -> goes to -> Base Compost / Regolith Inoculation [F: Regolith lacks organic nutrients]

3. Critical Dependency & Stress Test (The "Rug Pull")

Broken Node: Base Nuclear/Solar Grid (Power Drop)

- What happens: The grid diverts power away from the greenhouse to maintain critical life support in the crew quarters during a Martian dust storm.
- Map Effect: Draw a large red "X" through the arrow connecting the Base Grid to the LED Grow Lights.
- Consequence: Photosynthesis stops. The crop yield plummets, and ambient dome temperature drops, threatening a total crop freeze. The activity does not just pause; the demand shifts to emergency chemical heat packs or localized thermal blankets (which must now be added as emergency nodes).

4. Evidence Key Mapping

- [F] Sourced Fact: Water is a biological requirement; Martian regolith requires nutrient inoculation.
- [E] Estimate: 3-5 L/m^2/day water requirement (adapted from terrestrial hydroponics, assumes near-zero loss due to dehumidifier recapture).

- [A] Assumption: The base's HVAC system is designed to route crew CO2 directly to the agricultural dome.
- [?] Question: What is the specific electrical draw (in kilowatts) of the LED grow lights per square meter?

Earth Baseline Dependency Map (Commercial Greenhouse)

1. System Boundary & Core Action

- Activity: Sowing, maintaining, and harvesting potatoes in a commercial Earth greenhouse.
- Inside Boundary: Farmer, hand tools/machinery, potato crop, soil beds, drip irrigation lines.
- Outside Boundary (Support): Municipal water supply, local power grid, Earth's atmosphere, the Sun, commercial fertilizer supplier.

2. The Dependency Map (Nodes & Arrows)

Water & Hydration Flow

- Municipal Water / Local Well *(Outside Boundary)* -> supplies -> Greenhouse Irrigation System
- Greenhouse Irrigation System -> drips onto -> Topsoil
- Topsoil -> drains via -> Earth Gravity (1G) [F: Natural drainage prevents root rot] -> hydrates -> Potato Roots

Energy & Light Flow

- The Sun *(Outside Boundary)* -> enables -> Photosynthesis (Leaves) [F: Free, ambient resource]
- Local Power Grid *(Outside Boundary)* -> powers -> Supplemental Lights / Water Pumps

Air & Atmospheric Flow

- Earth Atmosphere *(Outside Boundary)* -> supplies -> Ambient CO2/O2 mix [F: Infinite, naturally balanced sink] -> breathes -> Potato Leaves

Waste & Output Flow (Open Loop)

- Potato Leaves -> transpires -> Humidity / Air Moisture

- Humidity -> vented via -> Roof Vents -> returns to -> Earth Atmosphere *(Outside Boundary)*
- Mature Potato Plant -> yields -> Tubers (Food) -> goes to -> Commercial Market
- Mature Potato Plant -> yields -> Inedible Biomass -> goes to -> Commercial Compost

3. Critical Dependency & Stress Test

Broken Node: The Sun (Seasonal shift / Cloud cover)

- What happens: Sunlight drops below required levels for optimal growth during winter months.
- Map Effect: The Sun node output is reduced, triggering demand on the Local Power Grid.
- Consequence: The system relies on grid-powered supplemental lighting. The crop survives, but operating costs increase. Unlike Mars, a total system collapse is avoided because the atmosphere and gravity still function entirely independently of the power grid.

Advanced Bioregenerative Life Support Systems: Engineering Martian Potato (*Solanum tuberosum*) Agriculture

Introduction to Bioregenerative Architectural Frameworks

The establishment of a permanent human presence on the Martian surface necessitates a fundamental transition from highly constrained, resupply-dependent logistical models to autonomous, closed-loop life support systems. Within this paradigm, Bioregenerative Life Support Systems (BLSS) emerge as the critical technological bridge, integrating mechanical infrastructure with biological processes to provide air revitalization, water reclamation, and continuous food production. The theoretical operational environment under analysis involves the sowing, maintaining, and harvesting of the potato (*Solanum tuberosum L.*) by an astronaut-farmer within a pressurized, climate-controlled agricultural dome on the Martian surface.

This agricultural boundary relies on an intricate web of localized and macro-systemic dependencies. Inside our operational boundary, the interactions between the farmer, hand

tools, the *Solanum tuberosum* crop, the immediate planter beds, local soil moisture and temperature sensors, and the irrigation drip lines touching the soil dictate the immediate success of the harvest. However, these localized actions are entirely subservient to critical support mechanisms outside our boundary: the base's primary nuclear or solar power grid, the central water recycling plant, and the dome's overarching Environmental Control and Life Support System (ECLSS), which includes HVAC and oxygen/carbon dioxide scrubbing[1].

The comparison between a terrestrial commercial Earth greenhouse and a Martian agricultural dome highlights severe operational deviations that dictate the engineering architecture of the system. Where Earth provides a biologically active, naturally draining soil matrix, 1G of gravitational pull to facilitate predictable capillary action, and a natural atmospheric pressure with abundant sunlight, the Martian environment provides a biologically dead regolith contaminated with toxic perchlorates, a reduced gravity of 0.38G, a near-vacuum external pressure, and significantly attenuated solar irradiation[3]. Consequently, the engineering parameters required to support *Solanum tuberosum* must transcend traditional agronomy, requiring highly specialized interventions in fluid dynamics, microbial bioremediation, and photon spectrum manipulation to ensure crew survival.

Human-Systems Integration and Environmental Constraints

The design and operation of an extraterrestrial agricultural dome must strictly adhere to the rigorous standards established by the NASA Human Integration Design Handbook (HIDH, NASA/SP-2010-3407) and the NASA Space Flight Human-System Standard (NASA-STD-3001)[1]. These foundational documents codify the acceptable thresholds for crew health, habitability, and human-system interfaces during long-duration space flight and planetary surface habitation[6].

The primary architectural driver of the Martian greenhouse is the mitigation of the ubiquitous hazards of spaceflight, particularly the vacuum of space, thermal extremes, and micrometeoroids[1]. The agricultural dome represents a critical single point of failure; a catastrophic breach in the primary pressure vessel would result in instantaneous depressurization, theoretically flash-freezing and killing the crop, thereby threatening the crew's food security. However, empirical research into the survivability of plants during rapid decompression events provides crucial operational tolerances for emergency protocols. Experiments utilizing specialized hypobaric chambers at the University of Guelph’s Controlled Environment Systems Research Facility (CESRF) have demonstrated that plant species can survive rapid decompression to absolute pressures as low as 1.5 kPa for up to thirty minutes, followed by re-pressurization, with negligible long-term impacts on fresh or dry mass accumulation[9]. While human astronauts require immediate isolation during such events, the physiological resilience of the crops suggests that automated, segmented blast

doors isolating damaged greenhouse modules can successfully preserve the agricultural yield if atmospheric pressure is restored within a brief, predefined window[9].

Resource Allocation and Dependency Mapping

The successful cultivation of potatoes on Mars requires the meticulous mapping of resources, their enabling functions, and their providers. The following matrix outlines the core biological and mechanical inputs required within the greenhouse boundary, categorized by their evidence status (Fact or Assumption).

Resource or Support	Enabling Function	Provider, Storage, or Maintenance	Evidence Status
Water	Seed hydration, nutrient transport, and cellular growth.	Base water recycling plant; local reservoir tank.	F (Fact - Biological requirement)
Light	Photosynthesis and thermal regulation.	Artificial LED grow lights powered by the base grid.	A (Assumption - Natural sunlight is insufficient)
Nutrients (N-P-K)	Plant development in otherwise dead regolith.	Base compost system or imported chemical fertilizer stores.	F (Fact - Regolith lacks organic nutrients)
CO2 / Airflow	Carbon intake for leaves; prevents mold buildup.	Dome HVAC and life support scrubbers routing crew exhalations.	A (Assumption - Crew CO2 is routed to the greenhouse)

A relevant output and waste flow from this system is the transpired humidity from the potato leaves. As the crop respires, massive volumes of water vapor float into the dome's airspace. This humidity must be captured by industrial dehumidifiers and routed back to the central water recycling plant to prevent catastrophic fungal outbreaks and to reclaim potable water. Simultaneously, inedible biomass, such as potato stems and leaves, represents a secondary waste flow that must be routed to the base compost processor for carbon and nutrient reclamation[10].

Stress-Testing the Photon Economy and Shared Resources

Within the BLSS architecture, electrical power represents a critical shared resource that the agricultural activity demands in high volumes. The high-intensity LED grow lights required for crop production compete directly with the base's primary life support systems, rover charging stations, and scientific equipment.

This leads to a critical dependency that must be stress-tested: natural Martian sunlight. Mars receives roughly 43% of the sunlight Earth receives, and global dust storms can block this diminished light for weeks or months at a time. If natural light fails entirely during a prolonged dust storm, and the base's primary power grid cannot spare enough electricity for continuous artificial lighting, the crop yield will plummet or the plants will die, directly threatening the crew's food security.

To change our interpretation of this catastrophic failure mode, we would require evidence demonstrating that *Solanum tuberosum* can be genetically engineered to thrive in ultra-low light conditions without artificial supplementation, or that highly efficient, ultra-low-power photon delivery systems can sustain minimal metabolic function during power rationing.

Systemic Estimation of Hydrological Demand

To design the local plumbing and reservoir architecture of the greenhouse, we must estimate the daily water requirement for the potato crop inside the boundary. The metric utilized is liters per square meter of crop per day ($L/m^2/day$).

Based on terrestrial commercial hydroponic potato farming data, adapted for a closed-loop system, a robust potato canopy utilizes approximately 3.4 to 5.2 $L/m^2/day$, with peak evapotranspiration rates approaching 10 $L/m^2/day$ during aggressive vegetative growth phases[12]. Because the plants actively filter this water through their root endodermis before transpiring it as pure water vapor, the greenhouse effectively acts as a massive biological distillation engine. The Martian system will require this same biological intake at the roots, but the overall system loss will be near zero if the dome's dehumidification hardware successfully recaptures 95% or more of the transpired moisture and routes it back to the central water grid.

This calculation relies on the assumption that the ambient temperature remains constant and the dehumidification hardware does not fail. Because the overall base relies heavily on this

continuous recycling loop, the greenhouse system requires a massive *reserve capacity* rather than just demand or capacity planning. If the central water recycling plant goes offline for emergency maintenance, the greenhouse's local reservoir must hold a multi-day reserve to keep the crop hydrated and alive until the main feed is restored.

Earth Versus Extraterrestrial Habitat Comparisons

The transposition of terrestrial agronomy to the Martian surface reveals stark contrasts in fundamental physical and chemical dependencies. The following table compares Earth conditions with the selected extraterrestrial habitat, detailing the severe consequences and necessary design implications for the Martian dome.

Dependency	Earth Condition	Habitat Condition (Mars)	Consequence and Design Implication
Growing Medium	Biologically active, nutrient-rich, naturally draining.	Martian regolith is biologically dead and contains toxic perchlorates.	Implication: Standard planting is impossible. The system requires a preliminary chemical or biological washing process to remove perchlorates, followed by inoculation using crew compost to create usable soil[3].
Gravity (Water Flow)	1G pulls water steadily downward through the	0.38G significantly alters capillary	Implication: Traditional overhead watering

	soil profile.	action, causing water to pool or drain unpredictably.	causes root rot or dry pockets. Irrigation must be redesigned as a pressurized, sub-surface drip line or an aeroponic misting chamber[4].
Atmospheric Pressure	1 ATM, naturally balanced CO2/O2 mix.	Near-vacuum outside; pressure and gas mix are artificially maintained inside.	Implication: The dome is a single point of failure. Micro-meteorite breaches will depressurize the dome. Design must incorporate automated, segmented blast doors to isolate damaged modules[9].

Fluid Hydraulics and Porous Media in Partial Gravity

The transport of water, oxygen, and nutrients through a solid porous medium is fundamentally dictated by the interplay of capillary forces, viscous forces, and gravitational pull. The shift from Earth's 1G to the 0.38G environment of Mars introduces severe complexities into soil hydrology, rendering traditional overhead watering or flood-and-drain irrigation systems completely unviable[4].

In a standard 1G environment, gravity acts as the dominant force pulling water steadily downward through the macro-pores of a soil profile, facilitating drainage and drawing fresh

oxygen into the root zone[15]. In a 0.38G environment, capillary forces dominate over gravitational forces, leading to erratic fluid distribution. This shift is mathematically quantified by the dimensionless Bond number (Bo), which measures the relative importance of gravitational forces to capillary forces. Under Martian gravity, the Bond number decreases significantly, meaning that larger pore sizes are required for gravity to overcome capillary retention[4]. Consequently, water applied from above will tend to pool at the surface or wick unpredictably through the substrate, filling macro-pores and causing catastrophic phase entrapment (air entrapment)[4].

Research examining liquid behavior in partially saturated porous media under variable gravity confirms that fluid displacement patterns become highly unstable in reduced gravity[4]. The conventional Richards equation, which describes liquid flow in unsaturated media, must be modified to account for the reduced gravitational term. Empirical data from parabolic flight experiments demonstrate that capillary-driven flow relies on numerous interfacial jumps, known as Haines jumps, which behave unpredictably without strong gravitational guidance[16]. The result is a high probability of localized hypoxia; roots surrounded by entrapped water will suffocate due to lack of oxygen diffusion, while adjacent roots may experience severe drought stress[17].

To circumvent the hydrodynamics of partial-gravity soil, space agriculture heavily investigates the use of soilless systems, particularly advanced aeroponics and pressurized subsurface drip networks. In a microgravity or partial-gravity aeroponic system, such as those modeled on the International Space Station's Veggie modules, plant roots are suspended in an enclosed, dark chamber devoid of solid media[14]. Below a physical divider, an ultrasonic vibrating plate or pressurized atomizer shears nutrient-enriched water into fine droplets in the micron range[14]. A forced-air circulation system then propels this mist directly across the suspended root mass. This approach completely eliminates the variables of capillary retention and phase entrapment associated with solid porous media, guaranteeing that roots receive optimal hydration and unrestricted atmospheric oxygen simultaneously[14]. Furthermore, aeroponics maximizes resource efficiency, utilizing up to 98% less water and significantly less fertilizer than soil-based cultivation[21].

The Martian Regolith Challenge: Geochemistry and Bioremediation

While aeroponics provides a highly efficient alternative to soil, the utilization of in-situ resources—specifically Martian regolith—remains a primary objective to reduce launch mass and establish true agricultural sustainability. However, early conceptual models positing the direct use of Martian regolith as a soil analogue have been challenged by planetary missions revealing a highly prohibitive geochemical reality. Martian regolith consists primarily of weathered basaltic rock, plagioclase feldspars, pyroxenes, and

olivine[22]. It is highly coarse-grained, devoid of biologically active organic matter, severely deficient in bioavailable nitrogen and phosphorus, and notably rich in iron and manganese[3].

Most critically, the regolith is contaminated with perchlorate salts (ClO_4^-), which constitute approximately 0.4 to 0.6 percent by weight of the superficial surface material[5]. Perchlorates are powerful, highly soluble oxidants that are profoundly toxic to humans, particularly affecting the thyroid gland, and promote the denaturation of macromolecules, oxidative stress, and DNA damage in plants[24]. If untreated, perchlorates inhibit seed germination, stunt root development, and accumulate within the potato tubers, rendering the crop lethal for human consumption[3].

To convert Martian regolith into a viable agricultural substrate, the perchlorates must be comprehensively neutralized. While mechanochemical washing is possible due to the high aqueous solubility of perchlorate salts, this method is highly resource-intensive, demanding vast volumes of purified water and resulting in the generation of concentrated toxic brines that must be stored or further processed[3].

Biological remediation presents a highly efficient, sustainable alternative. Dissimilatory perchlorate-reducing bacteria (DPRB) possess the unique metabolic capability to utilize perchlorate as a terminal electron acceptor under anaerobic conditions, reducing the toxic ClO_4^- to benign chloride (Cl^-) and oxygen[5]. A prominent candidate for this application is *Dechloromonas agitata*, a well-characterized strain containing the highly conserved perchlorate reductase ($pcrA$) and chlorite dismutase (cld) genes[5]. However, native terrestrial DPRB strains generally exhibit low resistance to ionizing radiation and desiccation, limiting their direct application in the volatile Martian environment where background radiation is significantly higher than on Earth[13].

To bridge this operational gap, synthetic biology has facilitated the hybridization of extremophiles. By extracting the perchlorate degradation gene clusters from *Dechloromonas agitata* and fusing them with constitutive expression promoters from *Deinococcus deserti*, researchers have successfully transformed the highly radiation-resistant bacterium *Deinococcus radiodurans* (strain R1) into a novel, chimeric organism designated as R1-CKB[13]. This engineered strain exhibits both exceptional radiation tolerance and robust perchlorate reduction capabilities, positioning it as the premier biological agent for large-scale regolith detoxification prior to crop planting[13].

Alternatively, non-biological physicochemical treatments such as Plasma-Activated Water (PAW) are being investigated. PAW, generated by subjecting water to cold atmospheric plasma, is rich in reactive oxygen and nitrogen species (RONS) and has been shown to improve seed germination and plant growth in simulated Martian regolith by altering the physical chemistry of the substrate[22].

Illumination, Photoperiods, and Tuberization Dynamics

Because Mars receives roughly 43% of the solar irradiation that Earth does, the Martian agricultural dome relies heavily on artificial Light Emitting Diode (LED) arrays. The photobiology of *Solanum tuberosum* dictates complex responses to light intensity, photoperiod duration, and spectral composition. Foundational research sponsored by NASA, particularly studies conducted by Raymond M. Wheeler, established the precise environmental parameters necessary for optimized potato yields in controlled life support systems[12].

Tuberization in potatoes is fundamentally a short-day response triggered by specific phytochrome interactions. However, intensive selective breeding and environmental manipulation have identified cultivars—such as Norland, Denali, and Russet Burbank—that tuberize aggressively even under continuous 24-hour light[12]. Potato yields in closed environments are directly correlated to the total quantity of photons absorbed per 24-hour period, a metric known as the Daily Light Integral (DLI)[28]. Research indicates that potato productivity approaches its maximum potential under lighting levels of 400 $\mu mol \cdot m^{-2} \cdot s^{-1}$ of Photosynthetic Photon Flux Density (PPFD) under continuous 24-hour lighting, or 800 $\mu mol \cdot m^{-2} \cdot s^{-1}$ under a 12-hour photoperiod[28].

The decision to utilize continuous light (CL) is a critical operational variable in space architecture. Operating LEDs continuously at lower intensities (400 $\mu mol \cdot m^{-2} \cdot s^{-1}$) rather than utilizing high-intensity pulses reduces the peak electrical load on the habitat's power grid and diminishes the acute thermal rejection burden placed on the HVAC cooling subsystems[29]. While continuous light causes severe stunting and leaf epinasty in intolerant cultivars like Kennebec and Superior, it yields exceptional results in tolerant strains, provided that the system implements a diurnal temperature fluctuation—specifically, cycling between 22°C during subjective "day" and 14°C during subjective "night"[28]. Tuberization itself is highly sensitive to heat, reaching maximum efficiency between 16°C and 20°C, and halting entirely if root-zone temperatures reach 28°C[28].

The spectral composition of the LED arrays also profoundly influences plant morphology and secondary metabolite production. The application of specific Red-Blue (RB) lighting ratios fundamentally alters the transcriptomic profile of the potato plant. Multi-omics analyses indicate that RB LED supplementation upregulates genetic pathways involved in photosynthesis, sugar metabolism, and polyamine biosynthesis, while simultaneously downregulating stress-related genes[30]. Tubers grown under tightly controlled RB spectra exhibit augmented levels of nitrogen, polyamines, and precursor amino acids, thereby qualifying their nutritional density for human consumption[30].

Furthermore, traditional overhead lighting results in dense upper canopies that shade the lower foliage, reducing overall stand efficiency. Advanced configurations deploy intracanopy lighting—vertical light bars interspersed directly within the foliage—to illuminate the lower leaf strata. Studies conducted at the University of Guelph's CESRF demonstrate that

manipulating light architecture in dense three-dimensional plant factories improves total biomass accumulation and delays the senescence of lower leaves, effectively increasing the harvest index of the crop[32]. Under optimized conditions, controlled environment potatoes exhibit extraordinary productivity. Peak yields have approached 19.7 kilograms of fresh mass per square meter, equating to nearly 200 tons per hectare, with a remarkably high harvest index (the ratio of edible tuber dry mass to total plant dry mass) of 0.7 to 0.8[12].

Closed-Loop Resource Cycling and Waste Valorization

A fully realized Bioregenerative Life Support System operates on the fundamental premise that there is no concept of waste; every output from one biological or mechanical process must serve as the input for another. Once the Martian regolith is purged of perchlorates, it must be inoculated with organic matter and macro-nutrients to support *Solanum tuberosum*. Human solid waste and crop residue, extensively composted, serves as the primary organic amendment, transforming the sterile mineral matrix into a biologically active living soil[34].

Despite the high harvest index of optimized potatoes, approximately 20% to 30% of the total dry mass consists of inedible stems, leaves, and roots[12]. In a closed-loop system, this cellulosic crop residue is diverted into an aerobic composting bioreactor[10]. The microbial decomposition of this biomass serves two critical functions: the reclamation of elemental nutrients (nitrogen, phosphorus, potassium) for reintegration into the hydroponic fertigation loop, and the generation of CO_2 [10].

Carbon dioxide enrichment is mandatory for high-yield space agriculture. While human respiration provides a baseline of CO_2 , the aggressive photosynthetic rates of a mature potato crop under continuous LED lighting rapidly deplete the atmospheric carbon within the dome. Modeling of compost-based closed-loop plant factories indicates that while crop residue composting alone can only produce a minor fraction (1.4% to 6%) of the total CO_2 required to maintain a targeted 1000 ppm concentration, integrating total station biowaste significantly offsets the need for imported compressed carbon[11].

The integration of biological waste requires strict pathogen management protocols. The utilization of advanced technologies, such as regenerative in situ electrochemical hypochlorination, ensures that pathogens like *Rhizoctonia solani* are eradicated from fertigation water and compost extracts before application to the crops[36]. By passing fertigation water through a specialized electrochemical cell featuring ruthenium oxide dimensionally stable anodes, free chlorine is generated *in situ*, effectively sterilizing the water column without the need to import heavy liquid chemical disinfectants from Earth[36].

Beyond agricultural reutilization, waste from the potato crop can be valorized for structural engineering. Recent materials science research has demonstrated the viability of "StarCrete," a novel building material composed of synthetic Martian regolith, potato starch, and a small amount of salt[37]. By extracting starch from surplus or dehydrated potatoes and

combining it with the local regolith, engineers have created a biocomposite exhibiting a compressive strength of 72 Megapascals (MPa)—more than twice as strong as ordinary terrestrial concrete (which averages 32 MPa)[37]. This implies that the agricultural dome can directly manufacture the building blocks required for habitat expansion, intimately linking the food supply to the physical infrastructure of the Martian colony.

Critical Literature and Methodology Review

The user parameters for this system analysis mandate the provision of supporting articles formatted according to the Modern Language Association (MLA) standards, accompanied by direct hyperlinks. To satisfy this requirement while maintaining the structural integrity of the report, the following table synthesizes the foundational research articles and handbooks that underpin the operational assumptions detailed throughout this analysis.

Author(s) & Year	Title and Journal	Direct Access URL	Formatted MLA Citation
Wheeler, R. M. (2006)	Potato and Human Exploration of Space: Some Observations from NASA-Sponsored Controlled Environment Studies. *Potato Research*, Vol. 49.	Link	Wheeler, Raymond M. "Potato and Human Exploration of Space: Some Observations from NASA-Sponsored Controlled Environment Studies." *Potato Research*, vol. 49, 2006, pp. 67-90.
Heinse, R. et al. (2009)	Liquid Behavior in Partially	Link	Heinse, Robert, et al. "Liquid

	Saturated Porous Media under Variable Gravity. *Soil Science Society of America Journal*, Vol. 73.		Behavior in Partially Saturated Porous Media under Variable Gravity." *Soil Science Society of America Journal*, vol. 73, no. 2, 2009, pp. 341-350.
Wamelink, G. W. et al. (2014)	Can Plants Grow on Mars and the Moon: A Growth Experiment on Mars and Moon Soil Simulants. *PLoS ONE*, Vol. 9.	Link	Wamelink, G. W. Wieger, et al. "Can Plants Grow on Mars and the Moon: A Growth Experiment on Mars and Moon Soil Simulants." *PLoS ONE*, vol. 9, no. 8, 2014, e103138.
Dsouza, A. et al. (2021)	A Conceptual Framework for Incorporation of Composting in	Link	Dsouza, Ajwal, et al. "A Conceptual Framework for Incorporation of

	Closed-Loop Urban Controlled Environment Agriculture. *Sustainability* , Vol. 13.		Composting in Closed-Loop Urban Controlled Environment Agriculture." *Sustainability* , vol. 13, no. 5, 2021, art. 2471.
Stoochnoff, J. et al. (2022)	Intracanopy lighting strategies to improve green bush bean compatibility with vertical farming. *Frontiers in Agronomy*, Vol. 4.	Link	Stoochnoff, Jared, et al. "Intracanopy Lighting Strategies to Improve Green Bush Bean (Phaseolus vulgaris) Compatibility with Vertical Farming." *Frontiers in Agronomy*, vol. 4, 2022.
NASA (2010)	Human Integration Design Handbook (HIDH). *NASA Special Publication*, NASA/SP-20	Link	National Aeronautics and Space Administratio n. *Human Integration Design Handbook (HIDH)*.

	10-3407.		NASA/SP-2010-3407, Baseline, 27 Jan. 2010.
NASA (2022)	Space Flight Human-System Standard Volume 2. *NASA Technical Standard*, NASA-STD-3001.	Link	National Aeronautics and Space Administration. *Space Flight Human-System Standard Volume 2: Human Factors, Habitability, and Environmental Health*. NASA-STD-3001, Rev. C, 2022.

Conclusion

The cultivation of *Solanum tuberosum* within a pressurized Martian dome extends far beyond the traditional parameters of terrestrial agronomy; it is an exercise in extreme, multidisciplinary systems engineering. The successful completion of a single agricultural cycle—from the preparation of the growing medium to the harvesting of mature tubers—relies on the seamless integration of biological processes with mechanical life support infrastructure.

The primary barriers to extraterrestrial agriculture are fundamentally physical and chemical rather than biological. The toxicity of Martian regolith requires the deployment of advanced synthetic biology, utilizing highly specialized extremophiles like *Deinococcus radiodurans* hybridized with *Dechloromonas agitata* to reduce oxidative perchlorates into inert chlorides. Furthermore, the disruption of capillary mechanics induced by a 0.38G gravitational field renders conventional soil-based irrigation severely compromised, forcing a necessary pivot toward two-chambered aeroponic misting systems or pressurized subsurface membranes to prevent phase entrapment and root hypoxia.

However, when these abiotic constraints are aggressively managed, the biological potential of the potato is unparalleled for spaceflight applications. Cultivars that tolerate continuous 24-hour LED illumination at precise photoperiodic intensities can produce immense caloric yields with unprecedented harvest indices, provided that strict diurnal temperature fluctuations are enforced to stimulate tuberization. Ultimately, the crop itself becomes an active, mechanical component of the habitat's life support matrix—acting as the primary distillation engine for water reclamation and the primary sink for anthropogenic carbon dioxide. Only through this absolute closure of resource loops—where inedible biomass is composted for CO2, humidity is captured for drinking water, and structural materials like StarCrete are synthesized from agricultural starch—can the theoretical concept of a Martian agricultural outpost become a sustainable operational reality.

Works cited

1. An Overview of Habitat Systems Supporting Human Spaceflight, https://www.worldscientific.com/doi/pdf/10.1142/9789811287695_0001?download=true
2. In-Situ Materials Processing Systems and Bioregenerative Life, https://ntrs.nasa.gov/api/citations/19930017506/downloads/19930017506.pdf
3. Fact-Checking "The Martian": Can You Really Grow Plants on Mars?, https://modernfarmer.com/2015/10/can-you-grow-plants-on-mars/
4. Liquid Behavior in Partially Saturated Porous Media under Variable, https://www.researchgate.net/publication/236856194_Liquid_Behavior_in_Partially_Saturated_Porous_Media_under_Variable_Gravity
5. A Multiplex Immunosensor for Detecting Perchlorate-Reducing, https://pmc.ncbi.nlm.nih.gov/articles/PMC7772991/
6. SP-2010-3407 NASA/ NASA SPECIAL PUBLICATION HUMAN, https://everyspec.com/NASA/NASA-SP-PUBS/SP-2010-3407_30301/
7. NASA-STD-3001, Volume 2, Revision F, https://www.nasa.gov/wp-content/uploads/2025/05/nasa-std-3001-vol-2.pdf?emrc%3D69db4b4ca7b6a
8. Nasa STD 3001 Vol 2 | PDF, https://www.scribd.com/document/92376322/Nasa-Std-3001-Vol-2
9. Plants survive rapid decompression: Implications for bioregenerative, https://www.researchgate.net/publication/229307977_Plants_survive_rapid_decompression_Implications_for_bioregenerative_life_support
10. A Conceptual Framework for Incorporation of Composting in Closed, https://www.mdpi.com/2071-1050/13/5/2471
11. (PDF) CO 2 demand-supply balance in a composting-based closed, https://www.researchgate.net/publication/365263259_CO_2_demand-supply_balance_in_a_composting-based_closed-loop_plant_factories
12. Potato and Human Exploration of Space: Some Observations from,

http://bigidea.nianet.org/wp-content/uploads/2018/07/Potato-Research-2006-Wheeler.pdf
13. Evidence for Biotic Perchlorate Reduction in ... - ResearchGate, https://www.researchgate.net/publication/331458075_Evidence_for_Biotic_Perchlorate_Reduction_in_Naturally_Perchlorate-Rich_Sediments_of_Pilot_Valley_Basin_Utah
14. MICROGRAVITY PLANT HABITAT - AgEcon Search, https://ageconsearch.umn.edu/record/344352/files/ijaer_10__02.pdf
15. (PDF) Microgravity Effects on Water Flow and Distribution in, https://www.researchgate.net/publication/11803815_Microgravity_Effects_on_Water_Flow_and_Distribution_in_Unsaturated_Porous_Media_Analyses_of_Flight_Experiments
16. Pore-Scale Wetting Process of Capillary-Driven Flow in Unsaturated, https://www.mdpi.com/2073-4441/14/13/1995
17. Measurements and Modeling of Variable Gravity Effects on Water, https://www.researchgate.net/publication/236856185_Measurements_and_Modeling_of_Variable_Gravity_Effects_on_Water_Distribution_and_Flow_in_Unsaturated_Porous_Media
18. Diffusion Aspects of Designing Porous Growth Media for Earth and, http://dx.doi.org/10.2136/sssaj2011.0438
19. Exploring Microgravity's Effect on Seed Germination and Growth of, https://journalijpss.com/index.php/IJPSS/article/download/5185/10574/7855
20. Aeroponic systems design: considerations and challenges, https://www.agroengineering.org/jae/article/view/1387/1073
21. soil based, aeroponic and hydroponic systems in space with, https://www.researchgate.net/publication/344138705_SOIL_BASED_AEROPONIC_AND_HYDROPONIC_SYSTEMS_IN_SPACE_WITH_MICROGRAVITY_AND_HYPOGRAVITY_CONDITIONS
22. Enhanced Plant Growth on Simulated Martian Regolith via Water, https://www.mdpi.com/1422-0067/26/17/8318
23. Sweet Potatoes on Mars - Botany One, https://www.botany.one/sweet-potatoes-on-mars/
24. Mining for Perchlorate Resistance Genes in Microorganisms From, https://pmc.ncbi.nlm.nih.gov/articles/PMC8343002/
25. Bioprospecting of extremophilic perchlorate-reducing bacteria - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC11246272/
26. The Science Behind The Martian: Can We Farm on Mars?, https://www.scienceworld.ca/stories/can-we-farm-on-mars/
27. Biogenic Palladium Improved Perchlorate Reduction during Nitrate, https://www.researchgate.net/publication/381159421_Biogenic_Palladium_Improved_Perchlorate_Reduction_during_Nitrate_Co-Reduction_by_Diverting_Electron_Flow_in_a_Hydrogenotrophic_Biofilm
28. Growth of Potatoes for CELSS - NASA Technical Reports Server,

https://ntrs.nasa.gov/api/citations/19950005536/downloads/19950005536.pdf?ref=restoremag.com
29. Continuous Lighting Promotes Plant Growth, Light Conversion, https://pmc.ncbi.nlm.nih.gov/articles/PMC8546256/
30. Growth, photosynthetic activity and tuber quality of two potato, https://www.researchgate.net/publication/329865596_Growth_photosynthetic_activity_and_tuber_quality_of_two_potato_cultivars_in_controlled_environment_as_affected_by_light_source
31. Enhancing tuber yield and nutraceutical quality of potato by ... - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC11931653/
32. Intracanopy lighting strategies to improve green bush bean, https://scispace.com/pdf/intracanopy-lighting-strategies-to-improve-green-bush-bean-3jcb270i.pdf
33. Intracanopy lighting strategies to improve green bush bean, https://www.frontiersin.org/journals/agronomy/articles/10.3389/fagro.2022.905286/full
34. Growing Plants in Martian Soil | Chicago Botanic Garden, https://www.chicagobotanic.org/blog/how-to/growing-plants-martian-soil
35. Building a living soil on Mars: Sequential phytoremediation and, https://research.buaa.edu.cn/zh/publications/building-a-living-soil-on-mars-sequential-phytoremediation-and-bi/
36. (PDF) Inactivation of Rhizoctonia solani in fertigation water using, https://www.researchgate.net/publication/336212163_Inactivation_of_Rhizoctonia_solani_in_fertigation_water_using_regenerative_in_situ_electrochemical_hypochlorination
37. Martian regolith mixture could prove stronger than concrete, https://www.astronomy.com/science/martian-regolith-mixture-could-prove-stronger-than-concrete/
38. Our homes on Mars could be made from potato-based 'StarCrete', https://www.popsci.com/technology/mars-starcrete-potato/